



ANTI WAX ADDITIVE (X01236D)

DESCRIPTION

Exocet® Anti Wax is formulated to improve the cold flow and handling properties of diesel and gas oil.

APPLICATION

Exocet® Anti Wax is typically added at the rate of 1 litre of additive to 1,000 litres of fuel.

The additive must be used as a preventative measure and will not work if the fuel is already waxed. Fuel-specific tests need to be carried out if a minimum operability temperature is required.

BENEFITS



FEATURES

- Boosts the fuel's resistance to waxing
- Allows operation at colder temperatures than fuel specification
- Inhibits the formation of wax crystals
- Reduces the potential for filter plugging
- Works with maximum allowable FAME contents

EXAMPLE PERFORMANCES

	EN590 DIESEL Summer	EN590 DIESEL Winter	CLASS A2 Gas Oil Summer	CLASS A2 Gas Oil Winter
CFPP* Specification	-5°C	-15°C	-4°C	-12°C
CFPP* with Exocet® Additive	-18°C	-26°C	-19°C	-28°C
Treat rate Additive:Fuel	1:1,000	1:1,000	1:1,000	1:1,000

* Cold Filter Plugging Point (CFPP)

WHEN TO USE

- As a prevention to fuel freezing and 'waxing out'
- Forecast is for temperatures of <-5°C
- At the transition between summer grade fuel and winter grade fuel to ensure full protection
- When winter grade fuel is required all year round

TREATMENT RATIO

1 litre of additive treats 1,000 litres of fuel

All Exocet® branded products are available in a range of sizes to 1,000 litres